

Concrete Hammers

CH-465



Input	1,050 W
Power	8.8 joules
Hammering Frequency	3,000 min ⁻¹
Shank Type	17 mm Hex
Overall Dimension	445 x 106 x 231 mm
Weight	5.1 kg

- * Quick retainer enables the bull point to be easily changed.
- * Automatic cut-off brush for longer tool life.
- * Built-in handle shock absorber decreased the vibration.
- * Grease packed lubrication provides long operation without special maintenance.
- * Durable aluminium die cast components are used in major parts.

CH-465 (19 mm EUR Shank)



Input	1,050 W
Power	8.8 joules
Hammering Frequency	3,000 min ⁻¹
Shank Type	19 mm Hex (EUR Shank)
Overall Dimension	445 x 106 x 231 mm
Weight	5.1 kg

- * 19 mm European shank model of CH-465.

CH-461



Input	1,050 W
Power	8.8 joules
Hammering Frequency	3,000 min ⁻¹
Shank Type	17 mm Hex
Overall Dimension	445 x 106 x 231 mm
Weight	5.1 kg

- * Spring retainer model of CH-465.

CH-485



Input	1,130 W
Power	15 joules
Hammering Frequency	1,800 min ⁻¹
Shank Type	21 mm Hex (STD / EUR Shank)
Overall Dimension	509 x 102 x 254 mm
Weight	8.5 kg

- * 21 mm hex shank model with high power motor.
- * Standard or European shank model is also available.
- * Automatic cut-off brush for longer tool life.
- * Grease packed lubrication provides long operation without special maintenance.
- * Durable aluminium die cast components are used in major parts.

CH-500N



Input	1,350 W
Power	42 joules
Hammering Frequency	1,200 min ⁻¹
Shank Type	30 mm Hex
Overall Length	728 mm
Weight	17.0 kg

- * 30 mm hex shank model for professional heavy duty use.
- * Automatic cut-off brush for longer tool life.
- * Grease packed lubrication provides long operation without special maintenance.

CH-500P



Input	1,250 W
Power	42 joules
Hammering Frequency	1,300 min ⁻¹
Shank Type	30 mm Hex
Overall Length	728 mm
Weight	16.7 kg

- * Double Insulation model of CH-500N.

Specifications

Model	Input	Power	Hammering Frequency	Shank Type	Overall Dimension	Weight
CH-465	1,050 W	8.8 joules	3,000 min ⁻¹	17 mm Hex	445 x 106 x 231 mm	5.1 kg
CH-465 (19 mm EUR Shank)	1,050 W	8.8 joules	3,000 min ⁻¹	19 mm Hex (EUR Shank)	445 x 106 x 231 mm	5.1 kg
CH-461	1,050 W	8.8 joules	3,000 min ⁻¹	17 mm Hex	445 x 106 x 231 mm	5.1 kg
CH-485	1,130 W	15 joules	1,800 min ⁻¹	21 mm Hex (STD / EUR Shank)	509 x 102 x 254 mm	8.5 kg

Model	Input	Power	Hammering Frequency	Shank Type	Overall Length	Weight
CH-500N	1,350 W	42 joules	1,200 min ⁻¹	30 mm Hex	728 mm	17.0 kg
CH-500P	1,250 W	42 joules	1,300 min ⁻¹	30 mm Hex	728 mm	16.7 kg