

Screw Drivers

E-3900A



| | |
|------------------|--|
| Input | 600 W |
| Bit Shank Size | 1/4" Hex |
| Applicable Screw | Maximum Diameter 4 mm Length 25 ~ 45 mm |
| Rotation Speed | 0 ~ 4,000 min ⁻¹ |
| Overall Length | 260 mm |
| Weight | 1.7 kg |

- * 4,000 min⁻¹ high speed screwdriver.
- * Millimetric stop adjustment for accurate screw-driving work.
- * Durable aluminium die casting gear case.
- * Hex bit holder.

E-3910A



| | |
|------------------|--|
| Input | 600 W |
| Bit Shank Size | 1/4" Hex |
| Applicable Screw | Maximum Diameter 4 mm Length 25 ~ 45 mm |
| Rotation Speed | 0 ~ 2,500 min ⁻¹ |
| Overall Length | 260 mm |
| Weight | 1.7 kg |

- * Slower speed model of E-3900A for screw-driving works which require more torque.

E-4000A



| | |
|----------------|-----------------------------|
| Input | 600 W |
| Bit Shank Size | 1/4" Hex |
| Rotation Speed | 0 ~ 2,500 min ⁻¹ |
| Overall Length | 260 mm |
| Weight | 1.7 kg |

- * Teks model of E-3910A.

SDR-401



| | |
|------------------|--|
| Input | 480 W |
| Applicable Screw | Maximum Diameter 4 mm Length 25 ~ 45 mm |
| Rotation Speed | 4,800 min ⁻¹ |
| Overall Length | 365 mm |
| Weight | 2.0 kg |

- * Screws are fed automatically for quick screw driving work.
- * The head is adjustable according to the length of the screw.
- * Accepts wide range of screws from 25 to 45 mm.



Specifications

| Model | Input | Bit Shank Size | Applicable Screw | Rotation Speed | Overall Length | Weight |
|---------|-------|----------------|--|-----------------------------|----------------|--------|
| E-3900A | 600 W | 1/4" Hex | Maximum Diameter 4 mm Length 25 ~ 45 mm | 0 ~ 4,000 min ⁻¹ | 260 mm | 1.7 kg |
| E-3910A | 600 W | 1/4" Hex | Maximum Diameter 4 mm Length 25 ~ 45 mm | 0 ~ 2,500 min ⁻¹ | 260 mm | 1.7 kg |
| E-4000A | 600 W | 1/4" Hex | - | 0 ~ 2,500 min ⁻¹ | 260 mm | 1.7 kg |
| SDR-401 | 480 W | - | Maximum Diameter 4 mm Length 25 ~ 45 mm | 4,800 min ⁻¹ | 365 mm | 2.0 kg |