



Technical drawing of a rectangular plate with dimensions and hole locations. The plate has a total width of 225 and a total height of 50. There are two rows of holes. The top row has a hole at the left edge (distance 0 from the left edge) and four holes at distances of 35, 40, 65, and 65 from the left edge. The bottom row has a hole at the left edge (distance 0 from the left edge) and four holes at distances of 35, 40, 65, and 65 from the left edge. The distance between the two rows of holes is 30. The distance from the right edge of the plate to the rightmost hole in both rows is 10. The drawing also shows a flange on the left side with a height of 10 and a flange on the top side with a height of 10. The drawing is labeled with dimensions: 10, 35, 40, 65, 65, 10, 30, 50, 225, R49, and R184.

Technical drawing of a mechanical assembly showing a side view and a top view. The side view shows a cylindrical component with a gear-like end and a flange. The top view shows the layout of the component with dimensions: 45, 35, 65, 35, 20, 24, and 55. A total length of 200 is indicated.

Technical drawing of a mechanical part (Fig. 1.10) showing a cross-section with dimensions: R70, 58, R56, 65, 40, 200, 65, and a 45° chamfer.



- トルク調整・速度調整およびトップピスト軸の操作を行うため、
部を※寸法で切欠いてください。
- 切欠き部の目隠しには付属の化粧ゴムプレートをご使用ください。
 (トップピスト軸調整用孔の目隠し用力バーは、お得意先にて手配をお願いします。)

