

GEOPRO Series Function

			Application		Concealed						Track-Rail					
			Model No.		GC-4V	GCS-4V	GCA-4V	GCAS-4V	GC-6V	GCS-6V	GT-4V	GTS-4V	GT-4PV	GTS-4PV		
Specifications			hold-open		—	○	—	○	—	○	—	○	—	○		
			Mechanism		Double Cylinder			Twin Cam			Double Cylinder					
			Installation		Concealed-in			Concealed-in			Pull side		Push side			
			Application Door size		Width(mm)	Weight(kg)										
					800	15 to 30	○	○			○	○				
					900	25 to 45	○	○			○	○				
					950	40 to 65	○	○		○	○	○				
					1050	60 to 85	○※	○※		○	○※	○※				
					1200	80 to 120				○						
					1500	100 to 140 up to 180				○	180kg (Max.Weight)					
Handing		Right hand or Left hand														
Material		Aluminum Alloy			Iron Casting			Aluminum Alloy								
Max.Opening angle	Standard		Offset hung : 105° Center hung : 110° Offset hung : 180° opening						160°		140°					
Durability			500,000 cycles													
Standard function			1st closing speed		○	○	○	○	○	○	○	○	○			
			2nd closing speed		○	○	○	○	○	○	○	○				
			Latching action		○	○	○	○	○	○	○					
			Delayed action		—	○	—	—	—	—	—					
			Back check		—	—	—	—	—	—	—					
			Closing force adjustment (#1~4)		○	○	—	○	○	○						
			Closing force adjustment (#3~6)		—	—	○	—	—	—						

※100Kg(Max.Weight)